



| Model | | CD-2 | CD-4 | CD-6 | CD-10 | CD-16 | CD-25 |
|--|-----|------|------|------|-------|-------|-------|
| Bağlama kapasitesi Capacity of clamp | Ton | 2 | 4 | 6 | 10 | 16 | 25 |
| Toplam strok (X) Total stroke (X) | mm | 8 | 8 | 8 | 8 | 8 | 8 |
| Pabuç strok (Y) Stroke of clamp (Y) | mm | 3 | 3 | 3 | 3 | 3 | 3 |
| Muhafaza edilen strok (Z) Preserved stroke (Z) | mm | 5 | 5 | 5 | 5 | 5 | 5 |
| Silindirin toplam hacmi Total volumn of cylinder | cc | 7.5 | 13 | 21 | 38 | 55 | 98 |
| Kalıp taban kalınlığı toleransı (H) The tolerance of the template thickness (H) | mm | ±2 | ±2 | ±2 | ±2 | ±2 | ±2 |

Hidrolik basınç / Hydraulic pressure : 250kgf/cm²

| Referans Nr. | A | B | C | D | E min. | F | G | W | N max. | T |
|--------------|----|----|-----|-----|--------|-----|----|-----|--------|---------|
| 1015-CD02 | 12 | 20 | 80 | 98 | 90 | 76 | 30 | 124 | 25 | M10x20D |
| 1015-CD04 | 12 | 25 | 100 | 109 | 93 | 87 | 30 | 135 | 30 | M12x24D |
| 1015-CD06 | 15 | 30 | 120 | 126 | 109 | 104 | 30 | 152 | 35 | M12x24D |
| 1015-CD10 | 15 | 35 | 150 | 148 | 131 | 124 | 36 | 174 | 40 | M14x28D |
| 1015-CD16 | 20 | 40 | 200 | 166 | 142 | 138 | 44 | 200 | 50 | M18x36D |
| 1015-CD25 | 20 | 45 | 235 | 200 | 163 | 168 | 48 | 240 | 60 | M22x45D |

Ürün Nr. 1015 Hidrolik Pabuç Model CD

• Standart Sıcaklık : 60°

Product Nr. 1015 Hydraulic Clamp Model CD

• Standard Temperature : 60°

Not

Pleyti dişi tezgahlarda kullanım olanağı sağlar.

Note

It can be used in machines with holes on the plate.

